

Retention time barrel RTB

General

After the homogeneous mixing of steam in a conditioner the product remains, during a preset length of time, in this heated and insulated retention time barrel. After the retention time barrel the product can be further treated in a pellet mill, extruder or meal cooler. The thermal treatment of the product results in an easier operation in the pellet mill, which simultaneously results in an improved pellet quality.


Advantages


- » guaranteed first-in/first-out of the mixture in the retention time barrel
- » up to 15% increase of pelleting capacity, due to higher temperature and improved absorption of steam
- » product is kept at required temperature
- » minimal formation of condensation
- » reduced growth of bacteria
- » easy to clean
- » simple design

Features

- » all components that come into contact with the product are from stainless steel AISI 304
- » solid shaft with large flight and inclined pitch
- » stuffing box sealings on shaft
- » direct drive or belt-driven by gear motor, suitable for frequency control. Frequency converter not included
- » large inspection doors with safety switch
- » temperature sensor PT 100
- » insulated with rock-wool
- » electric heating system with adjustable thermostat 30-110 °C.

Direct drive






| | | Di | Motor | | | |
|---------------|--------------------|-------|-------|-------|-------|---------------|
| Туре | Capacity (t/h*) | А | В | С | D | power (kW) |
| 1.250 x 4.000 | 26 | 1.530 | 1.645 | 4.900 | 3.510 | 2,2 |


^{*} With a retention time of 240 seconds





Belt driven





| | 01 | mensioi | Motor | | |
|--------------------|------------------|---|---|---|--|
| Capacity (t/h*) | А | В | С | D | power (kW) |
| 5 | 1.400 | 1.000 | 3.550 | 2.602 | 1,5 |
| 7 | 1.720 | 1.260 | 3.625 | 2.570 | 1,5 |
| 11 | 1.720 | 1.260 | 4.650 | 3.570 | 1,5 |
| 13 | 1.720 | 1.260 | 5.150 | 4.070 | 1,5 |
| 16 | 1.720 | 1.260 | 6.300 | 5.230 | 1,5 |
| | (t/h*) 5 7 11 13 | Capacity (t/h*) A 5 1.400 7 1.720 11 1.720 13 1.720 | Capacity (t/h*) A B 5 1.400 1.000 7 1.720 1.260 11 1.720 1.260 13 1.720 1.260 | Capacity (t/h*) A B C 5 1.400 1.000 3.550 7 1.720 1.260 3.625 11 1.720 1.260 4.650 13 1.720 1.260 5.150 | (t/h*) A B C D 5 1.400 1.000 3.550 2.602 7 1.720 1.260 3.625 2.570 11 1.720 1.260 4.650 3.570 13 1.720 1.260 5.150 4.070 |

^{*} With a retention time of 240 seconds



PTN produces and develops high-quality, reliable machines. It strives to provide its customers with the following benefits through its products:

- » Higher yields.
- » Lower energy consumption.
- » Low maintenance requirements.
- » Access to state-of-the-art technology.

As a globally operating, specialized manufacturer of pelletisers and related machinery it is our ambition to expand to become the most respected professional OEM (Original Equipment Manufacturer).

Our strategy for achieving this ambition is to:

- » Expand and consolidate the global network of professional sales and service points.
- » Create a virtual and real image of professionalism, quality and innovation as well as a high level of standardisation and digital accessibility for strategic partners.
- » Transform technology, know-how and competences into technical and commercial added value.
- » Generate stable growth in sales and profit.

